

Load Chart ATF-130 (เครื่อง 130 ตัน)

Outriggers fully extended (7.5 m)													
B \ A	12.8m*	12.8m	17.1m	21.4m	25.8m	30.1m	34.4m	38.7m	43.0m	47.7m	51.7m	56.0m	60.0m
2.7m	130.0**												
3.0m	111.2**	104.7**	90.00	90.00									
3.5m	99.70	95.70	90.00	90.00	70.00								
4.0m	91.40	88.10	88.00	87.60	70.00								
4.5m	83.30	81.50	81.40	81.00	70.00	54.30							
5.0m	75.80	75.80	75.70	75.30	70.00	51.30	44.00						
6.0m	66.30	66.20	66.10	65.60	66.00	50.00	42.30	32.80					
7.0m	58.80	58.10	58.30	57.50	58.10	49.30	38.40	32.80	27.10				
8.0m	52.70	51.20	51.60	51.40	51.10	46.00	38.00	32.80	27.10	21.40			
9.0m	47.70	45.40	45.80	45.80	45.30	43.10	35.80	30.30	27.10	21.40	16.60		
10.0m	42.10	40.60	41.00	41.00	40.50	40.60	33.70	28.10	26.50	21.40	16.60	13.20	
11.0m			37.00	37.00	36.50	37.20	31.80	26.20	24.70	21.40	16.60	13.20	10.60
12.0m			33.60	33.60	33.50	33.80	30.10	24.50	23.10	21.30	16.60	13.20	10.60
14.0m			28.20	28.10	28.70	28.30	27.20	21.60	20.40	19.20	16.60	13.20	10.60
16.0m				22.90	23.50	23.10	23.90	19.30	18.20	17.40	15.80	13.20	10.60
18.0m				19.20	19.70	20.60	20.00	17.40	16.70	15.70	14.50	12.80	10.60
20.0m					17.40	17.60	17.00	15.80	15.20	14.10	13.50	12.00	10.50
22.0m					15.50	15.30	14.70	14.10	13.90	12.70	12.20	11.20	9.70
24.0m						13.40	12.80	12.90	12.70	11.50	11.00	10.40	9.00
26.0m						11.80	11.30	11.80	11.30	10.50	10.00	9.80	8.20
28.0m							10.60	10.50	10.00	9.60	9.20	9.00	7.50
30.0m							9.80	9.40	8.80	8.60	8.40	8.30	6.90
32.0m								8.40	8.00	7.90	7.80	7.60	6.30
34.0m								7.60	7.50	7.40	7.10	7.10	5.80
36.0m									7.10	6.70	6.50	6.60	5.40
38.0m									6.50	6.00	6.10	6.00	5.00
40.0m									5.90	5.40	5.70	5.40	4.60
42.0m										4.90	5.20	4.80	4.30
44.0m										4.50	4.80	4.30	4.00
46.0m											4.30	3.90	3.80
48.0m											3.90	3.50	3.40
50.0m												3.00	3.10
52.0m												2.80	2.80
54.0m													2.40
56.0m													2.20

* Over rear / ** With additional lifting equipment

A = ระยะชิดบูม B = ระยะห่างตัว