

Load Chart GA-150N (เครื่อง 150 ตัน)

Outriggers fully extended (8.0 m)												
B \ A	12.6m		16.6m	20.7m	24.7m	28.8m	32.8m	36.9m	40.9m	45.0m	49.0m	53.1m
	2.7m	150.0*	120.00	40.00	36.20	38.80						
3.0m	130.0*	114.90	40.00	34.60	37.00							
3.5m	117.8*	105.40	40.00	32.20	34.40	30.30						
4.0m	103.2*	97.30	40.00	30.20	32.10	28.20						
4.5m	90.2*	90.20	39.10	28.40	30.10	26.40	28.50					
5.0m	82.3*	82.30	37.30	26.80	28.30	24.70	26.80	24.20				
6.0m	67.9*	67.90	34.10	24.00	25.20	22.00	24.00	23.40	20.70			
7.0m	57.5*	57.50	31.40	21.80	22.80	19.70	21.70	20.90	20.70	17.90		
8.0m	49.6*	49.60	29.20	19.90	20.70	17.90	19.80	18.90	20.50	17.90	16.00	
9.0m	43.3*	43.30	27.30	18.30	19.00	16.30	18.10	17.20	18.70	17.90	16.00	15.00
10.0m	32.3*	32.30	25.70	17.00	17.50	15.00	16.70	15.80	17.20	17.90	16.00	14.90
12.0m			23.10	14.80	15.20	12.80	14.40	13.40	14.70	15.80	16.00	14.50
14.0m			20.50	13.10	13.30	11.20	12.70	11.60	12.80	13.80	14.80	13.30
16.0m				11.80	11.90	9.90	11.20	10.20	11.30	12.20	13.10	12.20
18.0m				10.90	10.70	8.80	10.10	9.00	10.00	10.90	11.80	11.10
20.0m					9.80	7.90	9.10	8.00	9.00	9.80	10.60	10.20
22.0m					9.10	7.20	8.30	7.20	8.10	8.90	9.70	9.40
24.0m						6.60	7.60	6.50	7.40	8.10	8.80	8.60
26.0m						6.10	7.00	5.90	6.70	7.40	8.10	8.00
28.0m							6.40	5.40	6.20	6.80	7.50	7.40
30.0m							6.00	5.00	5.70	6.20	6.90	6.90
32.0m								4.60	5.30	5.70	6.40	6.40
34.0m								4.30	4.90	5.20	5.90	5.80
36.0m									4.60	4.80	5.40	5.00
38.0m									4.30	4.40	4.70	4.30
40.0m										4.10	4.10	3.70
42.0m										3.90	3.60	3.10
44.0m											3.10	2.60
46.0m											2.70	2.20
48.0m												1.80
50.0m												1.40
50.0m												
The maximum Load with out a pin	50.60	50.60	40.00	25.70	38.80	25.40	28.50	24.20	20.70	17.90	16.00	15.00
a (°)	0 - 81.5									2 - 81.5	5 - 81.5	8 - 81.5

* Over rear / ** With additional lifting equipment

A = ระยะชิดตอม B = ระยะห่างตัว a คือ องศาระเอบน