

Load Chart NK-500BV ( เครน 50 ตัน ช่วงยาว)

Outriggers fully extended (7.2 m)							
A \ B	10.8m	14.45m	18.1m	21.75m	25.4m	32.7m	40.0m
3.0m	50.50	28.00	28.00	24.00			
3.5m	42.20	28.00	28.00	24.00	18.00		
4.0m	37.00	28.00	28.00	24.00	18.00		
4.5m	33.00	28.00	28.00	24.00	18.00		
5.0m	30.20	28.00	28.00	24.00	18.00	13.00	
5.5m	27.50	26.50	25.60	23.20	18.00	13.00	
6.0m	25.00	24.00	23.50	21.50	18.00	13.00	
6.5m	22.70	22.30	21.80	19.90	18.00	13.00	7.50
7.0m	20.70	20.30	20.00	18.40	16.80	13.00	7.50
7.5m	18.90	18.60	18.50	17.10	15.70	13.00	7.50
8.0m	17.40	17.10	17.00	15.90	14.80	12.30	7.50
8.5m	15.95	15.70	15.60	14.65	14.00	11.60	7.50
9.0m	14.35	14.20	14.10	13.50	13.20	11.00	7.50
9.5m		12.80	12.70	12.55	12.45	10.50	7.50
10.0m		11.70	11.55	11.45	11.40	10.00	7.30
11.0m		9.75	9.60	9.50	9.45	9.10	6.80
12.0m		8.20	8.10	8.00	7.95	8.30	6.30
13.0m		7.00	6.85	6.75	6.70	7.55	5.90
14.0m			5.85	5.75	5.70	6.50	5.50
16.0m			4.25	4.15	4.10	4.95	4.70
18.0m				3.00	2.95	3.75	4.00
20.0m				2.10	2.05	2.80	3.30
22.0m					1.30	2.10	2.55
23.0m					1.00	1.80	2.25
24.0m						1.50	2.00
26.0m						1.05	1.50
28.0m						0.65	1.10
30.0m							0.75
31.0m							0.60
a (°)	0 ~ 82						

A = ระยะยื่นคานูม B = ระยะห่างตัว a คือ องศากระดาน