

Load Chart TG-1000R (เทรน 100ตัน)

Outriggers fully extended (8.2 m)							
B \ A	11.4m	17.0m	22.5m	28.1m	33.6m	41.0m	48.4m
3.0m	100.00	50.00	40.00				
3.5m	90.00	50.00	40.00				
4.0m	79.00	50.00	40.00	32.00			
4.5m	70.00	50.00	40.00	32.00			
5.0m	63.00	50.00	40.00	32.00	25.00		
5.5m	56.00	50.00	40.00	32.00	25.00		
6.0m	52.00	48.50	40.00	32.00	25.00	16.50	
6.5m	48.00	46.20	40.00	32.00	25.00	16.50	
7.0m	44.00	44.50	40.00	30.50	25.00	16.50	12.00
7.5m	40.50	41.00	40.00	28.70	25.00	16.50	12.00
8.0m	38.00	38.50	38.50	27.50	25.00	16.50	12.00
9.0m	33.00	33.50	33.50	25.00	23.00	16.50	12.00
10.0m		29.50	29.50	23.00	21.00	16.50	12.00
11.0m		26.00	26.00	21.00	19.10	16.50	12.00
12.0m		23.00	23.00	19.00	17.60	16.10	12.00
14.0m		17.00	18.00	16.00	14.90	13.80	11.70
16.0m			14.10	13.50	12.80	12.00	10.40
18.0m			11.10	11.10	10.80	10.50	9.40
20.0m			8.80	8.80	8.60	9.20	8.40
22.0m				7.00	7.00	8.00	7.40
24.0m				5.60	5.50	7.00	6.60
26.0m				4.50	4.30	6.00	5.90
28.0m					3.30	4.90	5.20
30.0m					2.50	3.90	4.60
32.0m						3.10	4.00
34.0m						2.30	3.20
36.0m						1.70	2.60
38.0m						1.10	2.00
40.0m							1.50
42.0m							1.00
a (°)	0 ~ 82						

A = ระยะขี้นุม B = ระยะห่างหัว a คือ องศากระดาน