

Load Chart TG-1200R (เครน 120ตัน)

Outriggers fully extended (8.2 m)							
B \ A	12.0m	17.7m	23.4m	29.1m	34.8m	42.4m	50.0m
3.2m	120.00	50.00					
4.0m	105.00	50.00					
4.5m	92.00	50.00	40.00				
5.0m	82.00	50.00	40.00				
5.5m	73.00	50.00	40.00				
6.0m	66.00	50.00	40.00	32.00			
6.5m	60.00	50.00	40.00	32.00	25.00		
7.0m	55.00	50.00	40.00	32.00	25.00	16.50	
7.5m	51.00	47.00	40.00	32.00	25.00	16.50	
8.0m	47.00	44.50	40.00	32.00	25.00	16.50	
8.5m	43.50	42.50	38.50	32.00	25.00	16.50	
9.0m	40.00	40.00	36.50	30.70	25.00	16.50	
10.0m	35.00	35.20	33.50	27.80	25.00	16.50	14.00
11.0m		31.20	30.10	25.40	23.00	16.50	14.00
12.0m		27.60	27.00	23.30	21.00	16.50	14.00
14.0m		21.40	21.80	19.60	17.60	16.50	12.60
16.0m		16.20	16.80	16.20	15.10	14.00	11.50
18.0m			13.20	13.40	12.90	12.10	10.50
20.0m			10.40	10.70	10.80	10.60	9.50
22.0m				8.50	8.70	9.30	8.60
24.0m				6.60	6.80	8.20	7.70
26.0m				5.00	5.20	6.90	7.00
28.0m					3.80	5.60	6.10
30.0m					2.70	4.40	5.50
32.0m					1.80	3.40	4.60
34.0m						2.60	3.70
36.0m						1.80	3.00
38.0m						1.20	2.30
40.0m							1.70
42.0m							1.20
a (°)	0 ~ 82						

A = ระยะชั้คบูม B = ระยะห่างตัว a คือ องศาระชนบูม