

Load Chart TG-1600M (เครื่อง 160 ตัน)

Outriggers fully extended (8.0 m)						
B \ A	17.5m	25.6m	33.7m	41.9m	46.0m	50.0m
3.3m	100.00					
3.5m	100.00	70.00				
4.0m	100.00	70.00				
4.5m	100.00	70.00				
5.0m	100.00	70.00	65.00			
5.5m	100.00	70.00	65.00			
6.0m	100.00	70.00	65.00	45.00		
6.5m	91.00	70.00	64.00	45.00		
7.0m	84.00	70.00	62.00	45.00	32.00	27.00
7.5m	78.00	69.00	60.00	45.00	32.00	27.00
8.0m	73.00	68.00	58.00	45.00	32.00	27.00
9.0m	64.00	65.00	53.00	45.00	32.00	27.00
10.0m	56.00	58.00	49.50	43.00	32.00	27.00
11.0m	49.00	51.50	46.00	41.00	32.00	27.00
12.0m	43.00	46.00	42.00	38.00	31.00	27.00
14.0m	35.00	36.00	36.00	32.00	28.00	25.00
16.0m		29.00	30.50	28.00	25.00	22.00
18.0m		23.00	25.00	24.00	22.50	20.00
20.0m		20.00	21.00	20.50	20.00	17.50
22.0m		16.50	17.50	17.00	18.00	16.00
24.0m			14.80	15.30	16.00	14.00
26.0m			21.00	12.80	13.80	12.70
28.0m			10.00	10.50	11.50	11.50
30.0m			8.00	8.50	9.50	10.50
32.0m				7.00	8.00	9.50
34.0m				5.50	6.70	8.30
36.0m				4.20	5.50	7.00
38.0m				3.00	4.20	5.80
40.0m					3.10	4.70
42.0m					2.20	3.80
44.0m						2.90
46.0m						2.10
47.0m						1.70

A = ระยะยึดมุม B = ระยะห่างตัว