

Load Chart TG-450M (เกรน 45 ตัน ช่วงยาว)

Outriggers fully extended (6.6 m)					
B \ A	10.4m	17.6m	24.7m	31.9m	39.0m
3.0m	45.00	27.00			
3.5m	40.50	27.00			
4.0m	36.50	27.00			
4.5m	33.00	27.00	18.00		
5.0m	30.20	27.00	18.00		
5.5m	27.50	24.90	18.00		
6.0m	25.00	22.90	18.00	12.00	
6.5m	22.70	21.20	18.00	12.00	
7.0m	20.00	19.50	16.75	12.00	
7.5m	17.80	17.80	15.65	12.00	6.50
8.0m	16.00	15.60	14.70	12.00	6.50
9.0m	12.80	12.80	12.80	10.75	6.50
10.0m		10.50	10.40	9.75	6.50
11.0m		8.60	8.55	8.90	6.50
12.0m		7.10	7.10	8.00	6.00
14.0m		5.00	5.00	5.80	5.15
16.0m		3.50	3.50	4.35	4.45
18.0m			2.40	3.25	3.70
20.0m			1.50	2.45	2.90
22.0m			0.75	1.70	2.20
24.0m				1.10	1.70
26.0m				0.60	1.20
28.0m					0.80
30.0m					0.45
a (°)	0 ~ 82				

A = ระยะชิดบูม B = ระยะห่างตัว a คือ องศากระดานบูม