

Load Chart TG-500M-5 (เครน 50 ตัน ช่วงยาว)

Outriggers fully extended (7.4 m)				
B \ A	10.65m	18.0m	25.3m	32.7m
3.0m	50.00	28.00		
3.5m	43.00	28.00		
4.0m	38.00	28.00	20.00	
4.5m	34.00	28.00	20.00	
5.0m	30.20	28.00	20.00	
5.5m	27.50	25.60	20.00	14.00
6.0m	25.00	23.50	20.00	14.00
6.5m	22.70	21.80	18.60	14.00
7.0m	20.70	20.00	17.30	13.50
7.5m	18.90	18.50	16.20	13.00
8.0m	17.40	17.00	15.30	12.50
8.5m	16.05	15.70	14.40	11.90
9.0m	14.90	14.70	13.60	11.30
10.0m		12.20	12.05	10.30
11.0m		10.20	10.05	9.40
12.0m		8.60	8.45	8.60
13.0m		7.30	7.20	7.90
14.0m		6.25	6.05	6.75
16.0m		4.50	4.35	5.15
18.0m			3.25	3.95
20.0m			2.30	3.05
22.0m			1.60	2.30
24.0m				1.70
26.0m				1.30
28.0m				0.85
30.0m				
32.0m				
34.0m				
a (°)			0 ~ 82	

A = ระยะยื่นบูม B = ระยะห่างตัว a คือ องศากระดุม



ชัชวารี เคนน โพร
CHAIAREE
CRANE **PRO**

40.0m
8.00
8.00
8.00
8.00
8.00
8.00
8.00
7.50
6.95
6.45
6.00
5.60
4.85
4.25
3.60
2.85
2.25
1.80
1.35
1.00
0.70
0.40



ชัยอารี เคน โปร

CHAIAREE

CRANE PRO