

Load Chart TL-200M-5 (เกรน 20 ตัน ช่วงยาว)

Outriggers fully extended (6.1 m)							
B \ A	9.8m	13.3m	16.9m	20.4m	23.9m	27.5m	31.0m
3.0m	20.00	17.50	14.50	9.50			
3.5m	20.00	17.50	14.50	9.50			
4.0m	18.00	17.50	14.50	9.50	7.50	6.50	
4.5m	16.30	15.80	14.50	9.50	7.50	6.50	
5.0m	14.85	14.40	13.25	9.50	7.50	6.50	6.00
5.5m	13.65	13.25	12.20	9.50	7.50	6.50	6.00
6.0m	12.30	12.20	11.30	9.50	7.50	6.50	6.00
6.5m	11.20	11.00	10.50	9.50	7.50	6.50	6.00
7.0m	10.25	10.00	9.80	8.85	7.50	6.50	6.00
7.5m	9.40	9.20	9.10	8.35	7.50	6.50	6.00
8.0m	8.65	8.45	8.35	7.90	7.20	6.25	5.70
9.0m		7.05	7.10	7.00	6.65	5.75	5.20
10.0m		6.05	5.90	6.30	6.20	5.30	4.75
12.0m			4.05	4.45	4.65	4.50	4.00
14.0m			2.90	3.25	3.45	3.55	3.50
16.0m				2.40	2.60	2.75	2.85
18.0m				1.75	2.00	2.10	2.20
20.0m					1.50	1.65	1.75
22.0m					1.05	1.25	1.35
24.0m						0.90	1.05
26.0m							0.75
28.0m							0.55
29.4m							0.40
a (°)	0 ~ 80						

A = ระยะยึดบูม B = ระยะห่างตัว a คือ องศากระดานบูม