

Load Chart TL-250M-4 ( เครื่อง 25 ตัน ช่วงยาว)

Outriggers fully extended (6.1 m)							
B \ A	10.5m	14.2m	18.0m	21.7m	25.5m	29.2m	33.0m
3.0m	25.00	20.00	16.00				
3.5m	25.00	20.00	16.00	12.00			
4.0m	22.90	20.00	16.00	12.00	11.50		
4.5m	21.00	20.00	16.00	12.00	11.50		
5.0m	19.40	18.40	16.00	12.00	11.50	9.00	
5.5m	17.70	16.80	14.75	12.00	11.50	9.00	7.00
6.0m	16.20	15.30	13.70	12.00	11.50	9.00	7.00
7.0m	13.70	12.65	11.95	11.00	10.00	9.00	7.00
8.0m	11.40	10.65	10.55	10.20	8.90	8.20	7.00
9.0m		8.85	8.75	9.20	8.05	7.45	6.25
10.0m		7.20	7.10	7.50	7.30	6.75	5.70
12.0m		5.00	4.90	5.25	5.60	5.65	4.80
14.0m			3.50	3.85	4.15	4.30	4.10
16.0m			2.50	2.85	3.15	3.30	3.40
18.0m				2.15	2.40	2.55	2.65
20.0m				1.60	1.85	2.00	2.10
22.0m					1.40	1.55	1.65
24.0m						1.20	1.30
26.0m						0.90	1.00
28.0m							0.75
30.0m							0.50
a (°)	0 ~ 82						

A = ระยะยึดคาน B = ระยะห่างตัว a คือ องศากระดาน