

Load Chart TR-250M-5 (เครน 4 ล้อ 25 ตัน)

Outriggers fully extended (6.3 m)				
B \ A	9.0m	15.0m	22.0m	28.5m
2.5m	25.00	19.40	12.50	
3.0m	25.00	19.40	12.50	
3.5m	25.00	19.40	12.50	8.00
4.0m	23.00	19.40	12.50	8.00
4.5m	21.20	18.00	12.50	8.00
5.0m	19.40	16.70	12.50	8.00
5.5m	17.80	15.50	11.70	8.00
6.0m	16.30	14.40	11.00	8.00
6.5m	15.10	13.40	10.40	8.00
7.0m		12.50	9.80	7.60
8.0m		10.70	8.70	6.90
9.0m		8.45	7.70	6.20
10.0m		6.95	6.80	5.65
11.0m		5.75	6.10	5.15
12.0m		4.85	5.40	4.70
13.0m		4.10	4.65	4.30
14.0m			4.00	4.00
15.0m			3.50	3.70
16.0m			3.10	3.40
17.0m			2.75	3.00
18.0m			2.45	2.70
19.0m			2.15	2.40
20.0m				2.15
22.0m				1.75
24.0m				1.40
26.0m				1.15
a (°)	0 ~ 82			

A = ระยะยื่นบูม B = ระยะห่างตัว a คือ องศาบูม