

Load Chart TR-350M-1 (เครน 4 ล้อ 35 ตัน)

Outriggers fully extended (6.6 m)					
B \ A	9.0m	15.25m	21.5m	27.75m	34.0m
3.0m	35.00	22.50			
3.5m	30.00	22.50	15.50		
4.0m	26.20	21.50	15.50	10.00	
4.5m	23.30	20.00	15.50	10.00	
5.0m	21.00	18.60	14.40	10.00	6.50
5.5m	19.00	17.50	13.50	10.00	6.50
6.0m	17.50	16.40	12.70	10.00	6.50
7.0m	16.00	15.50	12.00	9.40	6.50
8.0m		14.60	11.30	8.90	6.50
9.0m		12.30	10.10	8.00	6.40
10.0m		10.00	9.00	7.30	5.80
11.0m		8.20	8.00	6.70	5.30
12.0m		6.75	6.70	6.20	4.80
13.0m		5.70	5.70	5.70	4.40
14.0m		4.85	4.85	5.20	4.10
15.0m			4.15	4.60	3.80
16.0m			3.55	4.05	3.50
17.0m			3.05	3.60	3.30
18.0m			2.60	3.20	3.10
19.0m			2.20	2.80	2.90
20.0m			1.90	2.45	2.65
21.0m				2.15	2.40
22.0m				1.65	2.00
24.0m				1.25	1.60
26.0m					1.25
28.0m					0.95
30.0m					0.70
31.5m					0.50
a (°)	0 ~ 82				

A = ระยะขีดนม B = ระยะห่างค้ำ a คือ องศาขีดนม