

Load Chart TR-500M-2 ( เครื่อง 4 ล้อ 50 ตัน )

Outriggers fully extended (7.25 m)							
B \ A	9.7m	16.0m	22.3m	28.6m	34.9m	38.05m	41.2m
2.5m	45.00	30.00	20.00	12.00			
3.0m	45.00	30.00	20.00	12.00			
3.5m	45.00	30.00	20.00	12.00	10.00		
4.0m	39.50	30.00	20.00	12.00	10.00	8.00	
4.5m	35.50	30.00	20.00	12.00	10.00	8.00	
5.0m	32.00	28.00	20.00	12.00	10.00	8.00	6.00
5.5m	29.00	26.00	19.80	12.00	10.00	8.00	6.00
6.0m	26.50	24.10	18.70	12.00	10.00	8.00	6.00
6.5m	24.00	22.40	17.60	12.00	10.00	8.00	6.00
7.0m	22.00	20.60	16.70	12.00	10.00	8.00	6.00
8.0m		17.50	15.00	12.00	9.20	8.00	6.00
9.0m		14.20	13.40	11.50	8.50	8.00	6.00
10.0m		11.80	11.05	10.50	8.00	7.75	6.00
11.0m		9.80	9.20	9.50	7.60	7.25	6.00
12.0m		8.20	7.75	8.50	7.10	6.75	5.90
13.0m		7.00	6.60	7.40	6.70	6.30	5.50
14.0m			5.65	6.50	6.30	6.00	5.20
16.0m			4.15	4.90	5.30	5.30	4.60
18.0m			2.95	3.75	4.15	4.40	4.10
20.0m				2.90	3.30	3.50	3.60
22.0m				2.20	2.60	2.80	2.95
24.0m				1.60	2.05	2.30	2.35
26.0m				1.00	1.60	1.85	1.95
28.0m					1.20	1.40	1.60
30.0m					0.80	1.00	1.20
32.0m						0.65	0.85
34.0m							0.55
a (°)	0 ~ 82						

A = ระยะขีคานุม B = ระยะห่างตัว a คือ องศากระดานุม