

Load Chart TR-500M-3 (เครน 4 ล้อ 50 ตัน)

Outriggers fully extended (7.3 m)							
B \ A	9.7m	16.0m	22.3m	28.6m	34.9m	38.05m	41.2m
2.5m	50.00	30.00	20.00	12.00			
3.0m	50.00	30.00	20.00	12.00			
3.5m	45.00	30.00	20.00	12.00	11.00		
4.0m	39.50	30.00	20.00	12.00	11.00	8.50	
4.5m	35.50	30.00	20.00	12.00	11.00	8.50	
5.0m	32.00	29.00	20.00	12.00	11.00	8.50	7.00
5.5m	29.00	27.00	19.80	12.00	11.00	8.50	7.00
6.0m	26.50	24.60	18.70	12.00	11.00	8.50	7.00
6.5m	24.00	22.70	17.60	12.00	11.00	8.50	7.00
7.0m	22.00	20.90	16.70	12.00	11.00	8.50	7.00
8.0m		17.80	15.00	12.00	10.10	8.50	7.00
9.0m		14.60	13.40	11.50	9.40	8.50	7.00
10.0m		12.00	11.30	10.50	8.70	7.90	7.00
11.0m		10.00	9.40	9.50	8.10	7.35	6.50
12.0m		8.30	8.00	8.60	7.50	6.85	6.00
13.0m		7.10	6.80	7.40	7.00	6.40	5.60
14.0m			5.90	6.60	6.50	6.00	5.30
16.0m			4.20	5.00	5.40	5.30	4.70
18.0m			3.00	3.80	4.30	4.50	4.15
20.0m				2.95	3.40	3.55	3.60
22.0m				2.30	2.70	2.85	3.00
24.0m				1.65	2.10	2.30	2.40
26.0m					1.65	1.85	1.95
28.0m					1.25	1.40	1.55
30.0m					0.90	1.00	1.20
32.0m						0.70	0.90
34.0m							0.60
a (°)	0 ~ 82						

A = ระยะขีคานุม B = ระยะห่างตัว a คือ องศากระดานุม